

Color Options

Wood Grain



Bi-Directional American Walnut* Bi-Directional English Oak* Bi-Directional Ash* Bi-Directional Mahogany*



Uni-Directional American Walnut Uni-Directional English Oak Uni-Directional Ash Uni-Directional Mahogany



Uni-Directional Graywood Cedar Plank American Walnut Plank English Oak Plank


Plank and Bi-Directionals color options feature a light stucco embossment.
Uni-Directionals color options feature a wood grain embossment.

*Bi-Directional colors are available on 60, 61, 63, and 64 models with or without windows. They are only available on 71, 72, 73, 74, 81 and 82 models without windows.

Solid



Polar White Almond Sahara Tan Sandstone



Trinar® Beige Bronze Trinar® Brown Brown**



Espresso** Gray Charcoal Carbon Black**

**These colors include a cool chemistry paint finish but is not recommended for projects with extreme exposures to heat and sunlight.

Due to the printing process, colors may vary.
For accurate color samples, contact a Haas Door dealer for a color selector.

Panel Options



Flush Model 610

All colors except
Bi-Directional wood grains
Carriage Windows p24 & 25
Ranch Windows p24 & 26
TL Windows p26
Standard Windows p24 & 27
SlimLine Windows p26



V-Groove Model 612

All colors except
Bi-Directional wood grains
TL Windows p26
SlimLine Windows p26




Ribbed Short Panel Model 660

Carriage Windows p24 & 25
Model 672
Ranch Windows p24 & 26
Model 682
Standard Windows p24 & 27



Recessed Short Panel Model 661

Carriage Windows p24 & 25
Model 671
Ranch Windows p24 & 26
Model 681
Standard Windows p24 & 27



Ribbed Long Panel Model 664

Carriage Windows p24 & 25
Model 674
Ranch Windows p24 & 26

FEATURES

- 1³/₈" Thick with Full Thermal Break
- 0.106 Tested U-Factor
- Environmentally Compliant Polyurethane Insulation
- 26-Gauge Galvanized Steel
- Available with Wind Load & Impact Options
- Decorative Glass Options (pg 24)
- SelectView Options (pg 22-23)
- 35 Window Options (pg 25-27)
- Industry Leading Warranty (pg 30)
 - Lifetime Rust-Through & Delamination
 - Finish Warranty (pg 30)
 - 6 Year Hardware
 - 3 Year Spring
 - 1 Year All Other Components



A **Full Thermal Break** is used in the tongue-and-groove construction of all 600 series doors. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.





600 Series / 1 3/8" thick / 0.106 Tested U-Factor

668 in carbon black with 3-pane windows

LIMITED
LIFETIME
WARRANTY



Texas/Non-Texas
Wind Load
Impact/Non-Impact



Florida/Non-Florida
Wind Load
Impact/Non-Impact

MIAMI-DADE COUNTY
APPROVED



670 in graywood with plain windows



660 in bi-directional american walnut with 3-pane windows



ing Panel

Windows p24 & 25
Carriage Windows p24 & 26



Recessed Long Panel
Model 663

(Not available in 24" sections)
Carriage Windows p24 & 25
Model 673
(Not available in 24" sections)
Ranch Windows p24 & 26



Raised Ranch Panel
Model 670

Ranch Windows p24 & 26
Model 667 ◊
Carriage Windows p24 & 25
Model 687 ◊
Standard Windows p24 & 27



Raised Standard Panel
Model 680

Standard Windows p24 & 27
Model 668 ◊
Carriage Windows p24 & 25
Model 678 ◊
Ranch Windows p24 & 26



Raised Sculptured Panel
Model 690

Standard Windows p24 & 27
Model 669 ◊
Carriage Windows p24 & 25
Model 679 ◊
Ranch Windows p24 & 26

◊ = Due to variances in window sizes, not all window and panel stamp configurations align.

Insulated Steel