

# Color Options

## Wood Grain



Plank and Bi-Directionals color options feature a light stucco embossment. Uni-Directionals color options feature a wood grain embossment. \*Bi-Directional colors are available on 60, 61, 63, and 64 models with or without windows.

## Solid



\*\*These colors include a cool chemistry paint finish but is not recommended for projects with extreme exposures to heat and sunlight.

Due to the printing process, colors may vary. For accurate color samples, contact a Haas Door dealer for a color selector.

# Panel Options



### Flush Panel Model 2010

All colors except Bi-Directional wood grains  
Carriage Windows p25 & 27  
Ranch Windows p26 & 27  
TL Windows p26  
Standard Windows p24 & 27  
SlimLine Windows p26



### V-Groove Panel Model 2012

All colors except Bi-Directional wood grain & Plank options  
Carriage Windows p25 & 27  
Ranch Windows p26  
TL Windows p26  
SlimLine Windows p26



### Ribbed Short Panel Model 2060

Carriage Windows p25 & 27  
Model 2072  
Ranch Windows p26 & 27  
Model 2082 ◊  
Standard Windows p24 & 27



### Recessed Short Panel Model 2061

Carriage Windows p25 & 27  
Model 2071  
Ranch Windows p26 & 27  
Model 2081 ◊  
Standard Windows p24 & 27




### Ribbed Long Panel Model 2064

Carriage Windows p25 & 27  
Model 2074  
Ranch Windows p26 & 27

# FEATURES

- 2" Thick with Full Thermal Break
- 0.094 Tested U-Factor with an Air Infiltration Joint Seal that meets IECC Requirements
- Environmentally Compliant Polyurethane Insulation
- 26-Gauge Galvanized Steel
- Available with Wind Load & Impact Options
- Decorative Glass Options (pg 27)
- SelectView Options (pg 22-23)
- 37 Window Options (pg 24-27)
- Industry Leading Warranty (pg 30)
  - Lifetime Rust-Through & Delamination
  - Finish Warranty (pg 30)
  - 6 Year Hardware
  - 3 Year Spring
  - 1 Year All Other Components



2000 series doors include **Air Infiltration Seals**, which exceed the ASHRAE 90.1 Standard when installed with standard bottom seal and commonly available rigid/flexible vinyl door stop.

A **Full Thermal Break** is used in the tongue-and-groove construction. This rigid vinyl extrusion seals the joints and eliminates metal-to-metal contact, which limits the transfer of temperature.





**MIAMI-DADE COUNTY  
APPROVED**

Florida/Non-Florida  
**Wind Load**  
Impact/Non-Impact

Texas/Non-Texas  
**Wind Load**  
Impact/Non-Impact

LIMITED  
**LIFETIME  
WARRANTY**

2010 in cedar plank with slimline windows and selectview option (see pg 22)



2073 in polar white with prairie windows



2064 in uni-directional mahogany with 3-pane arch windows, hinges and handles



**Long Panel**  
Standard Windows p25 & 27  
Carriage Windows p26 & 27



**Recessed Long Panel**  
**Model 2063**  
(Not available in 24" sections)  
Carriage Windows p25 & 27  
**Model 2073** ◊  
(Not available in 24" sections)  
Ranch Windows p26 & 27



**Raised Ranch Panel**  
**Model 2070**  
Ranch Windows p26 & 27  
**Model 2067** ◊  
Carriage Windows p25 & 27  
**Model 2087** ◊  
Standard Windows p24 & 27



**Raised Standard Panel**  
**Model 2080**  
Standard Windows p24 & 27  
**Model 2068** ◊  
Carriage Windows p25 & 27  
**Model 2078** ◊  
Ranch Windows p26 & 27



**Raised Sculptured Panel**  
**Model 2090**  
Standard Windows p24 & 27  
**Model 2069** ◊  
Carriage Windows p25 & 27  
**Model 2079** ◊  
Ranch Windows p26 & 27

◊ = Due to variances in window sizes, not all window and panel stamp configurations align.