

CLOPAY COMMERCIAL - MODELS 906, 906U

architectural series



SLEEK ALUMINUM FULL-VIEW DOORS

Clopay Model 906 is available with a sleek panel design offering fewer lines and angles. The proportional rail and stile profiles, along with equal spacing, provide an aesthetically pleasing appearance. This sleek door is ideal in applications such as restaurants, auto dealerships and fire stations. In addition to these features, Model 906U features Intellicore® polyurethane insulated rails and stiles while still maintaining the sleek look.



Frame Detail



Section Joint Seal



Reinforcing Fin (where applicable)



Model 906U

Model 906

clopaycommercial.com

OPTIONS


PANEL OPTIONS AND CONFIGURATIONS



Aluminum Full-View Panel

Fewer panels than traditional aluminum doors allowing for a cleaner look. Solid aluminum panel not available.

MODELS 906 AND 906U – 7'6" TO 8'5" HIGH DOORS



Up to 9'0" Wide
1 Panel

9'1" to 17'2" Wide
2 Panel

17'3" to 22'2" Wide
3 Panel

FRAME COLOR OPTIONS



Clear Aluminum (Anodized)

Standard White (Painted)

Bronze (Painted)

Chocolate (Painted)

Bronze (Anodized)*



Black (Anodized)*



Dark Bronze (Anodized)*

* Additional cost and lead time may apply. The use of "Bronze (Painted)" is recommended due to slight color variation that may occur during the anodizing process.

GLASS OPTIONS



Clear Tempered Glass

Gray Tinted Tempered Glass

Midnight Gray Tinted Tempered Glass

Bronze Tinted Tempered Glass

Tempered Mirrored Glass

Clear Laminate Glass

White Laminate Glass

Gray Laminate Glass



Bronze Laminate Glass



Black Laminate Glass



Clear Acrylic



Frosted Acrylic



White Acrylic



Gray Acrylic



Bronze Acrylic



Black Acrylic*


* Available in 1/4" thickness only. Low-E glass options available. Hardcoated acrylic options available.

C-POWER™ ENABLED CLICK-TO-CONCEAL™ PANEL OPTIONS

Using discreet power and integrated technology to eliminate visible wires between sections, this film allows glass to transform from clear to opaque with a click of the remote. This option instantly shifts spaces from public to private, adapting to daylight, and enhancing visual security.

- Glazing Options – 5/8" Insulated Tempered Glazing and 5/16" Laminated Glazing
- Film Colors – White Opaque and Gray Opaque
- UV Protection – 99% UV Blocking

FILM COLOR OPTIONS:



White Opaque



Gray Opaque



Clear/White Opaque

PERFORMANCE OPTIONS

HEAVY-DUTY HARDWARE

- Double-end Hinge
- 3" Track

SPECIALTY PRODUCTS

- Exhaust Port

WINDCODE®

Design pressures (DP) up to 18 PSF depending on configuration. Models tested 50% greater than DP.



STANDARD SPECIFICATIONS

Max Width	22'2" (906) 20'2" (906U)
Max Height	16'0"
Exterior/Interior Panel Thickness	2-1/8"
Insulation	Intellicore® polyurethane (Model 906U)
End Stile Thickness	4.5" wide single up to 14'2" 6.5" wide double over 14'2"
Emboss	Recessed panel with smooth surface
Panel Style	Full-view
Section Construction	6063-T5 extruded aluminum alloy
Window Style	Full-view

GLASS AND PERFORMANCE SPECIFICATIONS

Glass	906/906U – Tempered glass, laminate glass and acrylic Tempered glass thicknesses of 1/8", 1/4" and 1/2" Acrylic thickness of 1/8" Laminate glass thickness of 1/4"	
Wind Load	Non-impact rated	
Joint Seal	Yes	
Springs	10,000 cycle springs Galvanized aircraft cable with minimum 7:1 safety factor	
Tracks	2" angle mount track with standard lift 3" track where applicable	
Hardware	TPE astragal in corrosion-resistant retainer Steel step plate and lift handle Inside slide lock for increased security	Commercial 10-ball steel rollers 11 gauge hinges
Warranty	Standard Paint – 5 Years Material and Workmanship – 1 Year	Color Blast® finish – 5 Years Hardware – 1 Year



For more information on these and other Clopay products, visit clopaycommercial.com. Architects and specifiers, visit architectdoorhelp.com.



©2026 Clopay Corporation. All rights reserved.



CMDC-906-25_REV0426